


STRAIGHT

DualSeal- mates with MIL-F-85421/1 and /2 (straight)


Hose	S/S Fitting#	A REF	B MAX	C REF	D MAX	THREAD SIZE	MATERIAL WT (LB) REF
SS							
R160-4	Y43004-72	.215	1.29	.562	.55	.4375-24	.06
R160-6	Y43006-72	.235	1.43	.688	.69	.5625-20	.08
R160-8	Y43008-72	.248	1.46	.875	.81	.7188-20	.12
R160-10	Y43010-72	.312	1.49	1.000	.93	.8438-18	.18
R160-12	Y43012-72	.352	1.76	1.125	1.19	1.0000-16	.29
R160-16	Y43016-72	.380	2.14	1.500	1.63	1.2500-14	.53



45° ELBOW

DualSeal- mates with MIL-F-85421/1 and /2 (45° elbow)

Hose	S/S Fitting#	A REF	B MAX	C REF	D MAX	E NOM	THREAD SIZE	MATERIAL WT (LB) REF
SS								
R160-4	Y43104-72	.215	1.90	.562	.54	.480	.4375-24	.07
R160-6	Y43106-72	.235	2.23	.688	.63	.570	.5625-20	.09
R160-8	Y43108-72	.248	2.30	.875	.75	.645	.7188-20	.14
R160-10	Y43110-72	.312	2.46	1.000	.87	.736	.8438-18	.19
R160-12	Y43112-72	.352	2.89	1.125	1.13	.788	1.0000-16	.34
R160-16	Y43116-72	.380	3.42	1.500	1.45	.917	1.2500-14	.67



90° ELBOW

DualSeal- mates with MIL-F-85421/1 and /2 (90° elbow)

Hose	S/S Fitting#	A REF	B MAX	C REF	D MAX	E NOM	THREAD SIZE	MATERIAL WT (LB) REF
SS								
R160-4	Y43204-72	.215	1.69	.562	.54	.825	.4375-24	.07
R160-6	Y43206-72	.235	2.10	.688	.63	1.062	.5625-20	.10
R160-8	Y43208-72	.248	1.93	.875	.75	1.210	.7188-20	.15
R160-10	Y43210-72	.312	2.07	1.000	.87	1.414	.8438-18	.20
R160-12	Y43212-72	.352	2.53	1.125	1.13	1.560	1.0000-16	.36
R160-16	Y43216-72	.380	3.07	1.500	1.45	1.888	1.2500-14	.68

Unless otherwise specified, all dimensions are in inches.