



# 240 Series Flared Fittings




## Flared fittings - mates with AS33656 / AS4395 and AS33657 / AS4396 (straight)

Hose	S/S Fitting#	A REF	B MAX	C REF	D MAX	THREAD SIZE	MATERIAL WT (LB) REF
R160-4	Y40004-72	.372	1.30	.562	.55	.4375-20	.07
R160-6	Y40006-72	.375	1.47	.688	.69	.5625-18	.09
R160-8	Y40008-72	.438	1.61	.875	.81	.7500-16	.15
R160-10	Y40010-72	.515	1.67	1.000	.93	.8750-14	.20
R160-12	Y40012-72	.562	1.91	1.250	1.19	1.0625-12	.36
R160-16	Y40016-72	.620	2.25	1.500	1.63	1.3125-12	.57
R160-20	Y40020-72	.620	2.81	1.812	2.06	1.6250-12	1.28
R160-24	Y40024-72	.765	3.17	2.125	2.46	1.8750-12	1.65



## Flared fittings - mates with AS33656 / AS4395 and AS33657 / AS4396 (45° elbow)

Hose	S/S Fitting	A REF	B MAX	C REF	D MAX	E NOM	THREAD SIZE	MATERIAL WT (LB) REF
R160-4	Y40104-72	.372	1.93	.562	.54	.348	.4375-20	.07
R160-6	Y40106-72	.375	2.07	.688	.63	.471	.5625-18	.11
R160-8	Y40108-72	.438	2.32	.875	.75	.572	.7500-16	.18
R160-10	Y40110-72	.515	2.56	1.000	.87	.643	.8750-14	.24
R160-12	Y40112-72	.562	2.99	1.250	1.13	.680	1.0625-12	.41
R160-16	Y40116-72	.620	3.75	1.500	1.45	.790	1.3125-12	.69



## Flared fittings - mates with AS33656 / AS4395 and AS33657 / AS4396 (90° elbow)

Hose	S/S Fitting	A REF	B MAX	C REF	D MAX	E NOM	THREAD SIZE	MATERIAL WT (LB) REF
R160-4	Y40204-72	.372	1.53	.562	.54	.642	.4375-20	.07
R160-6	Y40206-72	.375	1.84	.688	.63	.890	.5625-18	.11
R160-8	Y40208-72	.438	2.05	.875	.75	1.107	.7500-16	.19
R160-10	Y40210-72	.515	2.41	1.000	.87	1.281	.8750-14	.26
R160-12	Y40212-72	.562	2.77	1.250	1.13	1.405	1.0625-12	.45
R160-16	Y40216-72	.620	3.35	1.500	1.45	1.833	1.3125-12	.76

Unless otherwise specified, all dimensions are in inches.