



# 660 Series Flared Fittings



STRAIGHT

## Flared Fittings - mates with AS33656 / AS4395 and AS33657 / AS4396 (straight)


Hose	S/S Fitting#	A REF	B MAX	C REF	D MAX	THREAD SIZE	MATERIAL WT (LB) REF
R157-4	Y40004-22	.372	1.26	.562	.56	.4375-20	.07
R157-6	Y40006-22	.375	1.42	.688	.75	.5625-18	.12
R157-8	Y40008-22	.438	1.77	.875	.87	.7500-16	.20
R157-10	Y40010-22	.515	1.81	1.000	1.06	.8750-14	.25
R157-12	Y40012-22	.562	1.96	1.250	1.31	1.0625-12	.44
R157-16	Y40016-22	.620	2.16	1.500	1.63	1.3125-12	.65



45° ELBOW

## Flared Fittings - mates with AS33656 / AS4395 and AS33657 / AS4396 (45° elbow)

Hose	S/S Fitting	A REF	B MAX	C REF	D MAX	E NOM	THREAD SIZE	MATERIAL WT (LB) REF
R157-4	Y40104-24	.372	1.79	.562	.56	.348	.4375-20	.08
R157-6	Y40106-24	.375	2.09	.688	.75	.471	.5625-18	.14
R157-8	Y40108-24	.438	2.49	.875	.87	.572	.7500-16	.22
R157-10	Y40110-24	.515	2.82	1.000	1.06	.643	.8750-14	.30
R157-12	Y40112-24	.562	3.03	1.250	1.31	.680	1.0625-12	.50
R157-16	Y40116-24	.620	3.73	1.500	1.63	.790	1.3125-12	.73



90° ELBOW

## Flared Fittings - mates with AS33656 / AS4395 and AS33657 / AS4396 (90° elbow)

Hose	S/S Fitting	A REF	B MAX	C REF	D MAX	E NOM	THREAD SIZE	MATERIAL WT (LB) REF
R157-4	Y40204-24	.372	1.46	.562	.56	.642	.4375-20	.08
R157-6	Y40206-24	.375	1.77	.688	.75	.890	.5625-18	.14
R157-8	Y40208-24	.438	2.19	.875	.87	1.107	.7500-16	.23
R157-10	Y40210-24	.515	2.41	1.000	1.06	1.281	.8750-14	.32
R157-12	Y40212-24	.562	2.79	1.250	1.31	1.405	1.0625-12	.54
R157-16	Y40216-24	.620	3.30	1.500	1.63	1.833	1.3125-12	.84

Unless otherwise specified, all dimensions are in inches.